


SECTION
EXTERIOR WALL

LIGHTWEIGHT FOR EASY INSTALLATION
ELIMINATES THERMAL BRIDGING ON EXTERIOR
WALL APPLICATION
REDUCED AIR INFILTRATION
ECONOMICAL: LOW COST PER R-VALUE

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 4900-008.



APPLICATION DETAILS

FORTEFY THERMO RIGID INSULATION, APPLICATION DETAIL